



- VERIFICATION STATEMENT : This procedure was tested and verified at National Weather Service Headquarters, Silver Spring, Maryland (SLVM2).
- GENERAL : The attachments to this procedure contain the instructions to add output channel(s) to the CRS system.
- PROCEDURE : Attachment **A** provides procedures for implementing this modification. Attachment **B** (CRS Hardware Drawings) provides reference information. Attachment **C** provides verification of the new physical configuration (used before applying power). Attachment **D** provides a completed sample of a WS Form A-26, Maintenance Record.
- REPORTING INSTRUCTIONS : Report the completed modification on a WS Form A-26 according to the instructions in Engineering Handbook No. 4 (EHB-4), Engineering Management Reporting System (EMRS), Part 2, and Appendix I. Include the following information on the WS Form A-26:
- a. An equipment code of **CRSSA** in block 7.
  - b. A serial number of **001** in block 8.
  - c. A modification number of **57** in block 17a.
- A sample WS Form A-26 is provided as attachment **D**.

John McNulty  
Chief, Maintenance, Logistics, and Acquisition Division

Attachment A - Modification Procedure  
Attachment B - CRS Hardware Drawings  
Attachment C - New Configuration Physical Verification  
Attachment D - WS Form A-26 Sample

**Attachment A**  
**Modification Procedure**

## **Attachment A Modification Procedure**

### **Overview**

This modification note provides instructions for expanding a Console Replacement System (CRS) from a Large 6-channel configuration to a Large 7-channel configuration. The modification procedure contains seven parts:

1. CRS Power-Down Procedures
2. Equipment Upgrade Procedures
3. CRS Power-Up Procedures
4. CRS Login, Application Software Error Verification, and Test Database ASCII File Loading Procedures
5. Post Hardware Expansion Channel Operability Verification Procedures
6. Adding New Transmitter Channels and Editing Site Database ASCII File Procedures
7. ASM Alignment Procedures

- NOTE:**
1. Read the entire procedure, and verify receipt of all required parts before proceeding with the actual modification.
  2. Coordinate with the operations staff before performing this procedure.

**CAUTION**

**CRS must be down to perform the expansion modification. This modification contains test messages that should not be broadcast on any transmitter.**

**In addition, the database ASCII file will be recompiled, and all dictionary files will be lost! Switch to the backup NWR system, and ensure the dictionary files are backed up (see the *CRS System Administration Manual*) before performing this modification.**

## PART 1—CRS POWER-DOWN PROCEDURES

### 1.1 CRS Application Shutdown Procedure

1. Click on the **System** menu, and click on **Stop System**.
2. Wait until all icons on the *CRS System Status* menu turn **red**.

### 1.2 UNIX Shutdown Procedure

**NOTE:** 1. The shutdown of the CRS application is just one task before the graceful power-down. After stopping the CRS application software, implement a “controlled/orderly UNIX shutdown with NO automatic reboot” on the main processor (MP), and implement a “controlled/orderly UNIX shutdown” on all FEPs. Upon completion of the controlled/orderly UNIX shutdown, power-down the processors in the following order: MPs first followed by the FEPs.

1. Click on the **Maintenance** menu in the main CRS menu to access the *Maintenance* pull-down menu.
2. Click on **UNIX Shell** in the *Maintenance* pull-down menu. A *UNIX xterm* window pops up for the entry of UNIX commands.
3. Type the following UNIX command in the *xterm* window:  
**su root**
4. Press the **Enter** key. The shell responds with a prompt to enter root passwords.
5. Type the password for the root.
6. Press the **Enter** key. The shell prompt changes to a pound sign indicating all subsequent UNIX command entries have root authority.
7. Type the following UNIX command in the *xterm* window:  
**rsh 5MP /sbin/shutdown -i0 -g0 -y**
8. Press the **Enter** key. The shell command prompt returns after displaying a confirmation of shutdown initiation on 5MP. UNIX on processor 5MP shuts down.
9. Type the following UNIX command in the *xterm* window:  
**rsh 1FEP /sbin/shutdown -i0 -g0 -y**
10. Press the **Enter** key. The shell command prompt returns after displaying a confirmation of shutdown initiation on 1FEP. UNIX on processor 1FEP shuts down.

11. Type the following UNIX command in the *xterm* window:  
**rsh 2FEP /sbin/shutdown -i0 -g0 -y**
12. Press the **Enter** key. The shell command prompt returns after displaying a confirmation of shutdown initiation on 2FEP. UNIX on processor 2FEP shuts down.
13. Type the following UNIX command in the *xterm* window:  
**rsh 4BKUP /sbin/shutdown -i0 -g0 -y**
14. Press the **Enter** key. The shell command prompt returns after displaying a confirmation of shutdown initiation on 4BKUP. The UNIX on processor 4BKUP shuts down.
15. Type the following UNIX commands in the *xterm* window:
  - a. **cd /**
  - b. Press the **Enter** key.
  - c. Type **/sbin/shutdown -i0 -g0 -y**
  - d. Press the **Enter** key. Each CRS processor for the system may be safely powered-down when UNIX indicates shutdown is complete with the following message:  
**Press any key to reboot...**

**NOTE:** 2. Do not reboot any machine; go to section 1.3.

### 1.3 CRS Hardware Power-Down Procedure

Power-down all CRS equipment at the operator's station and in the equipment room by turning off the following:

<u>Operators Station</u>	<u>Equipment Room</u>
0MP and Monitor	4BKUP
5MP and Monitor	1FEP
NWRSAME (all)	2FEP
	LAN Bridge
	LAN Server
	Monitor
	Printer
	Audio switching assembly (ASA) power supplies
	Modem

## PART 2—EQUIPMENT UPGRADE PROCEDURES

### 2.1 1FEP and 4BKUP Setup Procedures

**NOTE:** Removing and replacing circuit cards must be accomplished in an antistatic work area using approved antistatic procedures.

1. Remove all cabling from 1FEP and 4BKUP, and remove FEPs from the equipment rack to the antistatic work area (see attachment **B**, figure A-5).
2. Remove the right side covers of the 1FEP and 4BKUP units using the following procedure:
  - a. Remove the right three screws located on the back of the system unit (see attachment **B**, figure A-1). These screws secure the right side access panel of the system to the chassis.
  - b. Pull the panel backward while lifting it upward.
3. Remove the screws holding expansion slot cover 5 on 1FEP and 4BKUP. Retain the screws (see attachment **B**, figure A-13).
4. Remove the expansion slot covers.

### 2.2 DECTalk Cards Input/Output (I/O) Address Configuration Procedure

1. Configure each new DECTalk card for the appropriate I/O address through switch 2 (SW2), as defined in table 1 and pictured in attachment **B**, figure A-11.

**NOTE:** 1. Depending on the CRS site configuration, there may be as many as five DECTalk cards per FEP located in slots 2 through 6.

**Table 1.** DECTalk Card Switch 2 (SW2) Settings

Module Number	SW2-1	SW2-2	SW2-3	SW2-4	SW2-5	SW2-6	I/O Address	PC Slot
4	off	off	off	off	on	on	380	6
3	off	off	on	on	off	on	360	5
2	on	off	on	off	off	on	328	4
1	off	on	off	on	off	off	250	3
0	off	off	off	on	off	off	240	2

**NOTE:** 2. Regardless of FEP, DECTalk card configuration remains constant, meaning modules 0, 1, 2, 3, and 4 are configured the same for each FEP.

2. Use table 1 to set up both DECTalk cards with the I/O address: 360. Install the DECTalk cards into slot 5 of 1FEP and 4BKUP, and reinstall a retaining screw.
3. Replace the 1FEP and 4BKUP covers, using the reverse procedure in section 2.1, step 2.

### 2.3 ASM Card Installation Procedure

1. Remove the ASA slot 7 cover by removing the two screws.

**NOTE:** There are five jumpers to be set on each ASM card.

2. Take the new ASM card (ASN: B440-2A6A3) and set the jumpers for slot 7 of the ASA in accordance with table 2.
3. Install the new ASM card into slot 7 of the ASA chassis and tighten the two screws.

**Table 2.** ASM Card Jumper Settings

	ASA Slot #	Silence Alarm Jumper "JP1"	ACP Channel Sel. Jumper "JP2" & "JP3"	BKUP Live/ Playback Cntrl Jumper "JP4"	FEP Select Jumper "JP5"
ASM 1 (channel 1)	1	EN (Enable)	1	BUL2	FEP1
ASM 2 (channel 2)	2	EN (Enable)	2	BUL2	FEP1
ASM 3 (channel 3)	3	EN (Enable)	3	BUL2	FEP1
ASM 4 (channel 4)	4	EN (Enable)	4	BUL2	FEP1
ASM 5 (channel 5)	5	EN (Enable)	5	BUL2	FEP2
ASM 6 (channel 6)	6	EN (Enable)	6	BUL2	FEP2
ASM 7 (channel 7)	7	EN (Enable)	7	BUL2	FEP2
ASM PB1 (mon/playback chan 1)	PB1	DIS (Disable)	PB1	PB	FEP1
ASM PB2 (mon/playback chan 2)	PB2	DIS (Disable)	PB2	PB	FEP2

## 2.4 DECTalk-ASM Audio Cable Installation Procedure


Using write-on cable labels, mark and connect the new and existing DECTalk-ASM audio cables on 1FEP and 2FEP in accordance with table 3.

**Table 3.** DECTalk to ASM Audio Cables

<b>From</b>	<b>To</b>	<b>Cable Label</b>
1FEP DECTalk 1 "J2" Port	ASM 1 "IN Port"	1-1
1FEP DECTalk 2 "J2" Port	ASM 2 "IN Port"	1-2
1FEP DECTalk 3 "J2" Port	ASM 3 "IN Port"	1-3
1FEP DECTalk 4 "J2" Port	ASM 4 "IN Port"	1-4
2FEP DECTalk 1 "J2" Port	ASM 5 "IN Port"	2-1
2FEP DECTalk 2 "J2" Port	ASM 6 "IN Port"	2-2
2FEP DECTalk 3 "J2" Port	ASM 7 "IN Port"	2-3
1FEP DECTalk 5 "J2" Port	ASM PB1 "IN Port"	1-5
2FEP DECTalk 5 "J2" Port	ASM PB2 "IN Port"	2-5

## 2.5 Operational and Spare ASC Jumper Setting and Cable Installation Procedure

1. Disconnect the DECTalk-ASC audio cables (labeled as 4-1, 4-2, 4-3, and 4-5).
2. Disconnect the two ACP-ASC audio cables.
3. Disconnect the ASC-4BKUP parallel port interface cables.
4. Disconnect the two ACP-ASC control cables.
5. Loosen the four front panel screws and extract the ASC card.
6. On both the operational and spare ASC, set the backup channel configuration using the seven jumpers on JP1. Using all seven jumpers, move the jumpers to the side of the block that lists the number of output channels for your site configuration, the center row of pins being common. Example: Using figure 1 as a reference, if your site configuration had 5, 6, 9, or 10 channels, each jumper would connect from the center row of pins to the top row of pins. If your site configuration had 1, 2, 3, 4, 7, 8, 11, 12, or 13 channels, each jumper would connect from the center row of pins to the bottom row of pins.



**Figure 1 ASM Card Jumper Block**

7. Insert the ASC back into the ASA and tighten the four front panel screws.
8. Reconnect the two ACP-ASC control cables.
9. Reconnect the ASC-4BKUP parallel port interface cable.
10. Reconnect the two ACP-ASC audio cables.
11. Using write-on cable labels, mark and connect the new DECtalk-ASC audio cable 4-4, and reconnect cables 4-1, 4-2, 4-3, and 4-5 in accordance with table 4.

**Table 4. DECtalk to ASC Audio Cables**

From	To	Cable Label
4BKUP DECtalk 1 "J2" Port	ASC "BKUP Audio 1" Port	4-1
4BKUP DECtalk 2 "J2" Port	ASC "BKUP Audio 2" Port	4-2
4BKUP DECtalk 3 "J2" Port	ASC "BKUP Audio 3" Port	4-3
4BKUP DECtalk 4 "J2" Port	ASC "BKUP Audio 4" Port	4-4
4BKUP DECtalk 5 "J2" Port	ASC "BKUP Audio 5" Port	4-5

**2.6 New Transmitter Audio Output Cables Installation Procedure**

1. Connect the "OUT 1" port of the new ASM card at slot 7 of the ASA chassis by installing the new audio output cable to the demarc panel position for the new transmitter.
2. Install the new NWRSAME (if available) into the top panel of the 5MP workstation (if available).

3. Install the NWRSAME-ACP interface cable from the NWRSAME rear connector to the "NWRSAME INPUT socket 1" port of the ACP2 rear panel; this connects to pins 2, 6, 7, 9, and 10 of the NWRSAME (if available).

**NOTE:** This completes the hardware modification.

## PART 3—CRS POWER-UP PROCEDURES

### \*\*\*WARNING\*\*\*

**Prior to powering up the FEPs, perform the *New Configuration Physical Verification* procedure contained in attachment C to verify proper system configuration. Failure to perform the procedure can assign transmitter broadcasts to incorrect output channels.**

#### 3.1 Power-Up FEP Procedure

1. Press the **ON/OFF** switch (located on the front center right of the enclosure) to power-up the FEPs. On each FEP, a green power LED lights up when the power is on. The FEPs can be powered up in any sequence. The FEPs go through a memory check, display the system configuration [as recognized by the basic I/O system (BIOS)], then boot the embedded operating system. At the completion of the boot process, the console screen displays the prompt:

#### **Console Login:**

The embedded operating system automatically initializes to a pre-set level and then waits for final start-up commands from the master MP.

**NOTE:** The FEPs share a common console through the *Shared Monitor Switch*. The console displays messages while completing the boot process of the FEP currently switched in.

2. Use the *Shared Monitor Switch* to select the next FEP. The console monitor displays:

**Press <F1> to resume, <F2> to Setup.**

3. Press **F1** to complete the boot process. The prompt displays:

#### **Console Login:**

4. Repeat for each remaining FEP.

### 3.2 Power-up Main Processors Procedure.

**NOTE:** 1. Power-up 0MP as the master main processor and 5MP as the shadowing processor.

Press the **ON/OFF** switch (located on the front center right of the enclosures) to power-up the MPs. A green power LED on each MP lights up when the power is on. The MPs can be powered-up in any sequence. The MPs go through a memory check, file system check, system configuration verification (as recognized by the BIOS), and then boot the embedded UNIX operating system. At the completion of the boot process, the workstation screen displays the *CRS Login* screen. The MPs are now ready for initialization of the CRS application software.

**NOTE:** 2. For Build 6.4 and higher: Following power-up, CRS displays the *Security Screen*. To continue the login process, click on the **Acknowledge** button.

3. Whenever the MPs are powered-up, they automatically step through the boot process to the multiuser mode without operator intervention.

## PART 4—CRS LOGIN AND TEST DATABASE ASCII FILE LOADING PROCEDURES

### 4.1 CRS Login Procedure

**NOTE:** 1. For Build 6.4 and higher: Following power-up, CRS displays the *Security Screen*. To continue the login process click, on the **Acknowledge** button.

2. The *CRS Login Screen* allows you to log onto CRS. This screen contains two fields: *Login ID* and *Password*. The fields are provided to allow you to type in your assigned login ID and password.

1. Type **admin** (for system administrator) in the *Login ID* field and press **Enter**. The cursor moves to the *Password* field.
2. Type in your assigned password, and press **Enter** to complete the CRS login process. The system displays the *CRS main* display. In addition, the system displays the following error message:  
**System is not operational. Perform 'Start CRS' to start system.**
3. Click on **OK** to clear the message.

**NOTE:** 3. The error message is only a status message indicating CRS is not running.

## 4.2 CRS Test Database ASCII File Loading Procedure

**NOTE:** 1. The following instructions for loading the CRS test database ASCII file assume everything is being done with OMP set as the MP.

1. Place the diskette with CRS test database ASCII files in the OMP diskette drive to copy the desired file from the diskette to CRS.
  - a. Type **dosdir a:** and press the **Enter** key to display a directory listing of the files on the test database diskette. There are 13 files on the diskette with the following filename convention:  
**TYP W\_CFG.ASC** where  $W = 1 - 4$   
**LRGX\_CFG.ASC** where  $X = 5 - 8$   
**MAXY\_CFG.ASC** where  $Y = 9$   
**MAXZ\_CF.ASC** where  $Z = 10 - 13$   
( $W$ ,  $X$ ,  $Y$ , and  $Z$  represent the number of transmitters supported by your CRS)
  - b. Locate the applicable test database ASCII file.
  - c. Type **doscp a:filename /crs/data/SS/filename** (where *filename* is the name of the CRS test database ASCII file to be used).
  - d. Press the **Enter** key.
2. Click and hold the left mouse button on any white space, move the cursor to select **XCRS\_SITE Utility**, and release the button to display the *XCRS\_SITE Utility* window.
3. Click on the **Select ASCII Site Setup** button to display the list of ASCII files.
4. Select the desired database ASCII filename copied from the diskette in section 4.2, step 1.c, and double click.

**NOTE:** 2. The directory selection block has a default directory name of */crs/data/SS*, and the file filter block has a default file name of */crs/data/SS/\*.ASC*. If the desired filename does not appear, it may have copied to the wrong directory in section 4.2, step 1.c. If that is the case, change the default directory name to the directory specified in section 4.2, step 1.c. The other reason the filename does not appear is because it is being filtered out. Remember, UNIX is case sensitive and if copied with an asc extension in lowercase, it does not display. Change the filter file name to */crs/data/SS/\*.asc*, and the filename displays.

5. Select **Initialize System Configuration and Database** to ensure the entire system database and configuration is erased and replaced.

6. Click on the **Start Site Configuration** button. The system displays:  
**Will now perform FULL site reconfiguration. Continue?**
7. Click on **OK**. The “wristwatch” and the “working” message display. Several messages scroll by. The last message reads:  
**Finished with site configure**  
The “wristwatch” and “working” message disappear. Ensure there are no error messages at the completion of the site configuration process.
8. Restart CRS by clicking on **Start CRS System**. The system displays:  
**The CRS system will be STARTED. Continue?**
9. Click on **OK**. The “wristwatch” and the “working” message display. Several messages scroll by. The last message refers to starting 4BKUP. The “wristwatch” and “working” message disappear.
10. Click on **Exit** to close the *XCRS\_SITE Utility* window.
11. Click on the **UNIX shell** window to select it. At the prompt, type **Exit** and press **Enter** to close the UNIX Shell.
12. Open the *System Status* window.
  - a. Click on **System**.
  - b. Click on **System Status**.
13. Monitor the *System Status* window and ensure the system is operational.

## **PART 5—POST HARDWARE EXPANSION CHANNEL OPERABILITY VERIFICATION PROCEDURES**

### 5.1 Channel Operability Verification Procedure

**NOTE:** CRS test database ASCII files contain test messages configured for continuous broadcast for channel operability verification.

1. Connect a monitor speaker or headphones to the ACP.
2. Using the *Channel Select* control, select each channel, one at a time, and monitor the output for the correct message (i.e., with channel one selected, the message output is: *This is transmitter one, audio switch module one*).

## 5.2 FEP Backup Mode Channel Operability Verification Procedure

1. Click on **Maintenance**.
2. Click on **Front-End Processor Switch**.
3. Select **1** in the *Front-End Processor Switch* window under *FEP*.
4. Select **Out** under *Switch*.
5. Select **Yes** under *Backup*.
6. Click on the **Save the current record** icon to execute the FEP switch process. The *Question* box displays:  
**Switch out the FEP FULLY offline ???**
7. Click on **OK** to continue. The system displays the “wristwatch” and the message:  
**Requesting FEP Switchout**
8. Monitor the *FEP1* and *BKUP* system status icons. Verify *FEP1* is in the backup mode and the *BKUP* icon displays the online status.
9. Upon completion of the FEP switch process, repeat section 5.1, steps 1 and 2.
10. Upon completion of the FEP backup mode channel operability verification, perform the following to display the *Front-End Processor Switch* window:
  - a. Click on **Maintenance**.
  - b. Click on **Front-End Processor Switch**.
11. In the *Front-End Processor Switch* window under *FEP*: select **1**.
12. Under *Switch*: select **IN** to switch *FEP1* back in.
13. Click on the **Save the current record** icon to execute the FEP switch process. The system displays the “wristwatch” and the message displays:  
**Requesting FEP switch-in...**
14. Monitor the *FEP1* and *BKUP* System Status icons. Verify *FEP1* is online and the *BKUP* icon displays the backup mode status.
15. When the system returns to normal operation, perform the following steps to close the *Front-End Processor Switch* window and stop CRS:
  - a. On the *Front-End Processor Switch* window:
    - 1) Click on **File**.
    - 2) Click on **Exit**.
  - b. On the *Main CRS* menu:
    - 1) Click on **System**.
    - 2) Click on **Stop System**.

- 3) Click on **OK**.
  - 4) Click on **Close**.
16. Monitor the *System Status* window and verify the CRS application has stopped.

## **PART 6—ADDING NEW TRANSMITTER CHANNELS AND EDITING SITE DATABASE ASCII FILE PROCEDURES**

### 6.1 Adding New Transmitter Channels Procedure

1. Click and hold the left mouse button on any white space, move the cursor to select **XCRS\_SITE Utility**, and release the button to bring up the *XCRS\_SITE Utility* window.
2. Click on **Select ASCII Site Setup** button to display the list of ASCII files.
3. Select the current site database ASCII file and double click.
4. Click on **Add Transmitter(s)** button to start the **addxmt** program. It displays the number of transmitters currently available, the next available transmitter to be added, and its appropriate processor and slot.
5. Use the following steps to add a new transmitter to the *Site Database ASCII* file:
  - a. **Mnemonic**
    - 1) Type option number **1** and press **Enter** to select *Mnemonic*.
    - 2) Type **a** and press **Enter** at the program prompt to add *Mnemonic*.
    - 3) Type **mmmm** and press **Enter** (where mmmm is the desired mnemonic), up to a length of 5 characters. The program returns the *Mnemonic*.
    - 4) Type **0** or press **Tab** and press **Enter** to complete the *Mnemonic* selection.
  - b. **Call Sign**
    - 1) Type option number **2** and press **Enter** to select *Call Sign*.
    - 2) Enter the **Call Sign** in the same manner as the *Mnemonic*, up to a length of 5 characters. The program returns the *Call Sign*.
    - 3) Type **0** or press **Tab** and press **Enter** to complete the *Call Sign* selection.
  - c. **Frequency**
    - 1) Type option number **3** and press **Enter** to select *Frequency*. The *Frequency* option only allows a selection of one of the seven choices listed.

- 2) Type **n** and press **Enter** (where n is the desired *Frequency* choice). The program returns the *Frequency* choice by displaying an asterisk (\*) next to the *Frequency* selection.
  - 3) Type **0** or press **Tab** and press **Enter** to complete the *Frequency* selection.
- d. **Location**
- 1) Type option number **4** and press **Enter** to select *Location*.
  - 2) Enter the *Location* (in the same manner as *Mnemonic* and *Call Sign*) up to a length of 40 ASCII characters. The program returns the *Location*.
  - 3) Type **0** or press **Tab** and press **Enter** to complete the *Location* selection.
- e. **Add Transmitter**
- 1) Type option number **5** and press **Enter** to use all the parameters defined in the first four steps to configure a new transmitter in the database ASCII file. The program indicates a new transmitter is needed.
  - 2) Type **y** and press **Enter**. The program returns the assignment of each transmitter to its proper processor and slot. The program indicates the appropriate database ASCII file has been updated and the original has been saved with the .SAV extension.
6. The program then asks if another transmitter is needed. If an additional transmitter is needed, repeat steps 6a through 6e for the next new transmitter. If not, type **n** and press **Enter** to exit the program.

## 6.2 Editing the Site Database ASCII File Procedure

1. When exit **addxmt** is done, the *Question* box displays:  
**Ready to recompile selected ASCII file. Continue?**
2. Click on **Cancel** to close the *Question* box.
3. Select **Initialize System Configuration and Database** to ensure the entire system database and configuration is erased and replaced.
4. Click on **Start Site Configure**. The *Question* box displays:  
**Will now perform FULL site reconfiguration. Continue?**
5. Click on **OK** to recompile the database ASCII file. Upon completion of the database ASCII file recompile process, the system displays:  
**Finished with site configure.**
6. Restart CRS by clicking on **Start CRS System**. The system displays:  
**The CRS system will be STARTED. Continue?**

7. Click on **OK**. The “wristwatch” and the “working” message display. Several messages scroll by. The last message refers to starting 4BKUP, and the “wristwatch” and “working” message disappear.
8. Click on **Exit** to close the *XCRS\_SITE Utility* window.
9. Open the *Alert Monitor* window:
  - a. Click on **System**.
  - b. Click on **Alert Monitor**.

**NOTE:** No attempt is made by **addxmt** to establish station identifiers, broadcast programs, broadcast suites, message types, voice parameters, keep-alive messages, interrupt messages, etc. for the new transmitters. These must be configured through the CRS graphical user interface (see the *CRS Site Operator’s Manual*) and updated in the site database ASCII file.

## PART 7–ASM ALIGNMENT PROCEDURES

**NOTE:** The output of each added ASM card must be aligned before the card is placed in service. The alignments must be performed in the following sequence:

1. Verify ACP **Ref.** Mark Alignment.
2. ASM Card Alignment.

### 7.1 Verify ACP Ref. Mark Alignment Procedure

**NOTE:**

1. The ACP Ref. mark alignment can be performed independently and does not require the use of any tool or equipment.
2. Transmitter x in this procedure refers to the channel under test.

1. Set up the CRS for Backup Live (BUL). No system database is required.
2. Set the index mark on the **tone volume control** knob to the *Ref.* position.
3. Push the **Transmitter x** and **Enable** buttons in sequence to start BUL on channel x. The buttons are located in the **BACKUP LIVE** block area on the ACP front panel.

**NOTE:** 3. Do not send audio to a transmitter while performing this procedure.

4. Push the **Alert Tone 1** button to generate the 1050 Hz warning alert tone (WAT).

5. Ensure the VU meter on the ACP front panel indicates **0 dBm**.

**NOTE:** 4. The duration of 1050 Hz WAT is 10 seconds.

6. Adjust the tone volume control for a reading of **0 dBm**.
7. Repeat steps 4, 5, and 6 as necessary to obtain a reading of **0 dBm**.

**NOTE:** 5. When the tone volume control is set to the true Ref. position, the ACP provides the selected WAT output level of **0 dBm**.

8. To stop BUL, first push the **Enable** button, then push the **Transmitter x** button.

## 7.2 ASM Card Alignment Procedure

**NOTE:** 1. This alignment requires two people: one in the operations room and one in the equipment room.

2. When performing any of the following alignments, the system's output(s) must be disconnected from the telecommunications link and terminated into a 600-ohm load. All audio signal level measurements are taken across the 600-ohm load.

1. Assemble the following required equipment:
  - dB Meter to read the audio signal level
  - small jeweler's screwdriver
  - 600-ohm dummy load with RJ-11 plug attached
2. Set up the CRS for BUL. No system database is required.
3. Set the index mark on the **tone volume control knob** to the *Ref.* position.
4. Push the **Transmitter x** and **Enable** buttons in sequence to start BUL on channel x. The buttons are located in the **BACKUP LIVE** block area on the ACP front panel.
5. Plug the RJ-11 connector (with the 600-ohm load attached) into the RJ-11 jack of **OUT 1** on the ASM of transmitter x (output channel x).
6. Connect the dB meter across the 600-ohm load.
7. Push the **Alert Tone 1** button to send a WAT to the **OUT 1** jack of ASM card 1.
8. Measure and record the signal level in dB across the 600-ohm load.
9. Using a small jeweler's screwdriver, adjust the transmitter gain control potentiometer through the ASM front panel until a reading of **0 dBm** is obtained across the 600-ohm load.

**NOTE:** 3. Table 5 provides equivalent V rms and V p-p values related to dBm (all referenced to 600-ohms) as an aid in referencing readings taken with measurement equipment that may not read directly in dBm.

**Table 5.** Voltages vs dBm (into 600-ohm load)

dBm	RMS	P-P	dBm	RMS	P-P	dBm	RMS	P-P
10	2.440	6.93	-4	0.480	1.35	-17	0.110	0.301
9	2.183	6.17	-5	0.430	1.20	-18	0.097	0.270
8	1.946	5.50	-6	0.390	1.03	-19	0.087	0.240
7	1.734	4.90	-7	0.345	0.96	-20	0.0775	0.215
6	1.546	4.37	-8	0.306	0.85	-21	0.690	0.194
5	1.377	3.89	-9	0.275	0.76	-22	0.061	0.170
4	1.228	3.47	-10	0.245	0.68	-23	0.054	0.152
3	1.094	3.01	-11	0.213	0.61	-24	0.048	0.135
2	0.975	2.75	-12	0.192	0.54	-25	0.043	0.120
1	0.869	2.46	-13	0.173	0.48	-26	0.039	0.108
0	0.775	2.15	-14	0.154	0.43	-27	0.034	0.09622
-1	0.690	1.94	-15	0.138	0.38	-28	0.031	0.085
-2	0.610	1.70	-16	0.125	0.34	-29	0.028	0.076
-3	0.540	1.52				-30	0.024	0.068

**NOTE:** 4. The WAT output from the ACP nominally lasts 10 seconds. It is recommended a second person push the **Alert Tone1** button for a near continuous tone output. This smooths the calibration effort and minimizes the time required.

5. Primary (Out1) and secondary (Out2) outputs are two independent outputs. However, the output level of Out1 is affected by approximately 1.5 dB if Out2 is loaded.

6. During BUL, the VU meter monitors the ACP tone output, not the output of the ASM card. The ACP tone output is sent to the ASM card via the ASC for final output.

10. Repeat steps 7, 8, and 9 as necessary to obtain a reading of **0 dBm** for the channel under test.

11. To stop BUL, first push the **Enable** button and then push the **Transmitter x** button.
12. Repeat steps 1 through 10 to align each of the new ASM cards in the system.
13. Activate each ASM card output by pushing the respective **Transmitter x** button and then the **Enable** button.

## **Attachment C**

### **New Configuration Physical Verification**

## Attachment C New Configuration Physical Verification

### 7-Channel System

#### Required MPs, FEPs, DECtalks, ASC, and ASMs

The Large 7-channel system has 2 MPs (0MP and 5MP), 3 FEPs (1FEP, 2FEP, and 4BKUP), 14 DECtalk cards, 1 ASC card, and 10 ASM cards:

0MP	main processor 1		
5MP	main processor 2		
1FEP	front end processor 1		
	LAN Card	LAN interface	(slot 1)
	DECtalk 1	channel 1	(slot 2)
	DECtalk 2	channel 2	(slot 3)
	DECtalk 3	channel 3	(slot 4)
	DECtalk 4	channel 4	(slot 5)
	DECtalk 5	PB1	(slot 6)
2FEP	front end processor 2		
	LAN Card	LAN interface	(slot 1)
	DECtalk 1	channel 5	(slot 2)
	DECtalk 2	channel 6	(slot 3)
	DECtalk 3	channel 7	(slot 4)
	DECtalk 5	PB2	(slot 6)
4BKUP	backup front end processor		
	LAN Card	LAN interface	(slot 1)
	DECtalk 1	backup channel 1 or 5	(slot 2)
	DECtalk 2	backup channel 2 or 6	(slot 3)
	DECtalk 3	backup channel 3 or 7	(slot 4)
	DECtalk 4	backup channel 4	(slot 5)
	DECtalk 5	backup PB1 or PB2	(slot 6)
ASA	audio switch assembly		
ASC	audio switch controller		
	ASM 1	channel 1	(slot 1)
	ASM 2	channel 2	(slot 2)
	ASM 3	channel 3	(slot 3)
	ASM 4	channel 4	(slot 4)
	ASM 5	channel 5	(slot 5)
	ASM 6	channel 6	(slot 6)
	ASM 7	channel 7	(slot 7)
	ASM PB1	monitor/playback channel 1	(slot PB1)
	ASM PB2	monitor/playback channel 2	(slot PB2)
	ASM Spare	spare	(slot S)

## DECtalk Card Configurations

There is one I/O jumper to be set on each DECtalk card:

	<b>FEP Name</b>	<b>FEP EISA Slot #</b>	<b>I/O Address Jumper</b>
1FEP DECtalk 1 (channel 1)	1FEP	2	240
1FEP DECtalk 2 (channel 2)	1FEP	3	250
1FEP DECtalk 3 (channel 3)	1FEP	4	328
1FEP DECtalk 4 (channel 4)	1FEP	5	360
1FEP DECtalk 5 (mon/playback chan 1)	1FEP	6	380
2FEP DECtalk 1 (channel 5)	2FEP	2	240
2FEP DECtalk 2 (channel 6)	2FEP	3	250
2FEP DECtalk 3 (channel 7)	2FEP	4	328
2FEP DECtalk 5 (mon/playback chan 2)	2FEP	6	380
4BKUP DECtalk 1	4BKUP	2	240
4BKUP DECtalk 2	4BKUP	3	250
4BKUP DECtalk 3	4BKUP	4	328
4BKUP DECtalk 4	4BKUP	5	360
4BKUP DECtalk 5	4BKUP	6	380

## ASM Card Configurations


There are five jumpers to be set on each ASM card:

	ASA Slot #	Silence Alarm Jumper "JP1"	ACP Channel Sel. Jumper "JP2" & "JP3"	BKUP Live/ Playback Cntrl Jumper "JP4"	FEP Select Jumper "JP5"
ASM 1 (channel 1)	1	EN (Enable)	1	BUL2	FEP1
ASM 2 (channel 2)	2	EN (Enable)	2	BUL2	FEP1
ASM 3 (channel 3)	3	EN (Enable)	3	BUL2	FEP1
ASM 4 (channel 4)	4	EN (Enable)	4	BUL2	FEP1
ASM 5 (channel 5)	5	EN (Enable)	5	BUL2	FEP2
ASM 6 (channel 6)	6	EN (Enable)	6	BUL2	FEP2
ASM 7 (channel 7)	7	EN (Enable)	7	BUL2	FEP2
ASM PB1 (mon/playback chan 1)	PB1	DIS (Disable)	PB1	PB	FEP1
ASM PB2 (mon/playback chan 2)	PB2	DIS (Disable)	PB2	PB	FEP2

## ASC Card Configuration

There is a 7-by-3 matrix switch to be set up on each ASC card:

Set the backup channel configuration using the seven jumpers on JP1. Using all seven jumpers, move the jumpers to the side of the block that lists the number of output channels for your site configuration, the center row of pins being common. Example: Using **Figure 1** as a reference, if your site configuration had 5, 6, 9, or 10 channels, the jumpers would connect from the center row of pins to the top row of pins. If your site configuration had 1, 2, 3, 4, 7, 8, 11, 12, or 13 channels, the jumpers would connect from the center row of pins to the bottom row of pins.



**Figure 1 ASM Card Jumper Block**

## Cable Label Between DECtalk Card and ASM Card

From	To	Cable Label
1FEP DECtalk 1 "J2" Port	ASM 1 "IN Port"	1-1
1FEP DECtalk 2 "J2" Port	ASM 2 "IN Port"	1-2
1FEP DECtalk 3 "J2" Port	ASM 3 "IN Port"	1-3
1FEP DECtalk 4 "J2" Port	ASM 4 "IN Port"	1-4
2FEP DECtalk 1 "J2" Port	ASM 5 "IN Port"	2-1
2FEP DECtalk 2 "J2" Port	ASM 6 "IN Port"	2-2
2FEP DECtalk 3 "J2" Port	ASM 7 "IN Port"	2-3
1FEP DECtalk 5 "J2" Port	ASM PB1 "IN Port"	1-5
2FEP DECtalk 5 "J2" Port	ASM PB2 "IN Port"	2-5

### Cable Label Between DECtalk Card and ASC Card

<b>From</b>	<b>To</b>	<b>Cable Label</b>
4BKUP DECtalk 1 "J2" Port	ASC "BKUP Audio 1" Port	4-1
4BKUP DECtalk 2 "J2" Port	ASC "BKUP Audio 2" Port	4-2
4BKUP DECtalk 3 "J2" Port	ASC "BKUP Audio 3" Port	4-3
4BKUP DECtalk 4 "J2" Port	ASC "BKUP Audio 4" Port	4-4
4BKUP DECtalk 5 "J2" Port	ASC "BKUP Audio 5" Port	4-5

## **Attachment D**

### **WS Form A-26 Sample**

WS FORM A-26 (4/94)		U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION NATIONAL WEATHER SERVICE				Document Number <b>G 49986</b>			
<b>ENGINEERING MANAGEMENT REPORTING SYSTEM MAINTENANCE RECORD</b>									
<b>General Information</b>		1. Open Date <b>1 / 02 /01</b>	Time <b>0900</b>	2. Initials <b>JMM</b>	3. Response Priority (check one) <input type="radio"/> Immediate <input type="radio"/> Low <input type="radio"/> Routine <input checked="" type="radio"/> Not Applicable		4. Close Date    Time <b>1 / 02 /01 1100</b>		
5. Description <b>Expand CRS from a Large 6 to a Large 7 Configuration</b>									
<b>Equipment Information</b>		6. Station ID <b>EWX</b>	7. Equipment Code <b>CRSSA</b>	8. Serial Number <b>001</b>		9. TM <b>M</b>	10. AT <b>M</b>	11. How Mal. <b>999</b>	
12. EQUIPMENT OPERATIONAL STATUS TIMES		a. Fully Operational <input type="text"/>	b. Logistics Delay <input type="text"/>	Partly Operational    c. All Other <input type="text"/>		d. Logistics Delay <input type="text"/>	Not Operational    e. All Other <input type="text"/>		
<b>13. Parts Failure Information</b>							<b>14. Work Load Information</b>		
Block #	a. ASN	b. NSN	c. TM	d. AT	e. How Mal.	f. Qty.	g. Maint. Hrs.	Type	Staff Hrs.
1								a. Routine	
2								b. Non-Routine	
3								c. Travel	
4								d. Misc.	<b>2:00</b>
5								e. Overtime	
<b>Miscellaneous Information</b>		15. Maintenance Comments <b>Installed 2 DECTalk cards and 1 ASM card to expand CRS from a Large 6 to a Large 7 configuration, I.A.W. Mod Note 57</b>						16. Initials <b>JMM</b>	
17. SPECIAL PURPOSE REPORTING		a. Mod. No. <b>57</b>	b. Mod./Act./Deact.Date <b>1/02/01</b>	c.		d.		e.	
18. CONFIGURATION MGMT. REPORTING (use as directed)		ASN		Vendor Part No. (New Part)		Serial Number (Old Part)		Serial Number (New Part)	

D-1

EHB-7  
Issuance 01-04  
1/26/01

Attachment D